



15395 AZT

ADJUSTABLE WIDE FLOOD LIGHT

Large (6 $\frac{3}{4}$ " x 5") floodlight with wide beam spread for dramatic wall washing in a vertical installation.

SPECIFICATIONS

Housing Durable die-cast aluminum construction. Heat-resistant flat glass is fully sealed.

Finish Textured Architectural Bronze

Wiring 35' of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt bi-pin, high temperature porcelain socket.

Light Bulb 75-W. Max. 50-W. QT4 (15550CLR) supplied

Mounting Accessories Included
8" In-ground stake

Optional Mounting Accessories

15656, 15657 or 15658 – Stems

15649 – Stem Coupler

15601 – Surface Mounting Flange

15607 – Tree/Surface
Mounting Bracket

Bulk Pack

15395AZT6 – Bulk Pack includes
8" ground stakes

Vertical Illuminance (FC)

Mounting Distance from Surface	A	B	C	D	E	F
3'	9.30	5.43	1.81	.9	.18	.09
4'	5.08	3.05	1.01	.51	.10	.05
5'	3.25	1.95	.65	.33	.07	.03
6'	2.26	1.35	.45	.23	.05	.02
7'	1.66	.99	.33	.17	.03	.03
8'	1.27	.76	.25	.13	.03	.01
9'	1	.6	.2	.1	.02	.01
10'	.81	.49	.16	.08	.02	.01

Aluminum only light bulb conversion:
75W, T4 BIPIN, FCX154

***See pages 119–121 for more light bulb options.**

Vertical Illuminance on Wall (FC)

